

Portable CO2



Note:
Model SN.C 2KG, SN.C 5KG
Approved

AL-SANAD Portable Carbon Dioxide Fire Extinguishers are known for its high reliable performance and ease of handling. The cylinder for CO2 Fire Extinguishers are seamless and extruded from high grade Chrome Molybdenum Steel or Manganese Steel or Carbon Steel.

Carbon Dioxide is discharged as a white cloud of snow which throttles a fire by eliminating the oxygen. Designed to protect areas where class B (flammable liquids and gases) or Electrical class of fires could occur.

Technical Specifications:

- ☞ Extinguishing Agent : CO2
- ☞ Test Pressure : 250 Bar
- ☞ Coating : Electrostatic Polyester Powder
- ☞ Storage Temperature :-20°C to +60°C

Class of Fire:



Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



Fires on electrical plants.

Model	SN.C 2KG	SN.C 5KG
Capacity	2 Kg	5 Kg
Total Weight	6.3 Kg	16.3 Kg
Total Height (mm)		755
Total Width (mm)	176	190
Cylinder Height (mm)	510	600
Cylinder Diameter (mm)	130	145
Hose Length (mm)	Only horn	1220
Maximum Effective Range (m)		5
Duration of Discharge (Sec)	9-11	9-11