

FLOW CONTROL EQUIPMENT



Code No.
HYD096-DI-XXX-UL

Swing Check Valve

- ◆ Connection Ends : Flange to BSEN 1092-21997
- ◆ Working Pressure : PN10/16
- ◆ Temperature Range : 0°C-100°C
- ◆ Coating Fusion Bonded Epoxy Coating in accordance with ANSI/AWWA C550
- ◆ Size available from 50mm to 200mm



Code No.
SPR189-DI-XXX-UL

Wafer Check Valve

- ◆ Connection Ends : BS EN 1092 PN10/PN16/PN25, AS2129 TABLE E, JIS B2212 10K, BS 10 TABLE D/E
- ◆ Working Pressure : PN10/16
- ◆ Temperature Range : 0°C-100°C
- ◆ Coating : Fusion Bonded Epoxy Coating in accordance with ANSI/AWWA C550
- ◆ Size available from 50mm to 400mm



Code No.
SPR266-D50-UL

Supervisory Switch MXHQ D50-UL

- ◆ Dimensions : D50 (2"-16")
- ◆ Design Standard : UL 346, ULC-S548, FM 3135
- ◆ Working Temperature : -10~80 °C
- ◆ Electrical Ratings : 15 Amps at 125/250VAC
- ◆ Ingress Protection : IP65

Part No.	Part	Standard Specification
1	Enclosure	ADC12
2	Brace	Carbon Steel Q235
3	Micro Switch	
4	Base	ADC12
5	Connection plate	Carbon Steel Q235
6	Lever	AISI 304
7	Axis	Nylon
8	Gasket	CR foam cotton
9	Pressing sleeve	PTFE
10	Rubber ring	EPDM
11	The fastening plate	Carbon Steel Q235