



AL-SANAD Mobile Foam Fire Extinguisher, available in stored pressure model (TF) and external high pressure CO2 cartridge model (TFC). Manufactured using special cold rolled steel and the cylinder is painted with electrostatic polyester powder.

This unit is easy to use and can be used by one person, suitable to keep in factories and warehouses, as well as petrol stations. The AFFF will quickly seal the surface of a liquid fire to prevent re-ignition.

Class of Fire



A Solid matters forming glowing residues. e.g. wood, rubber (car tires), paper, textiles.



B Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.

Note:

Model SN.F25, SN.F50
Approved

CAUTION:

NOT FOR USE ON LIVE
ELECTRICAL EQUIPMENT



Model	SN.F25	SN.F50
Capacity	25 Ltr	50 Ltr
Total Weight	51.5 Kg	82 Kg
Total Height (mm)	990	1010
Total Width (mm)	455	555
Total Depth (mm)	665	695
Hose Length (mm)	3000	5000
Maximum Effective Range (m)	8	8
Duration of Discharge (Sec)	19-23	38-42
Extinguishing Agent	AFFF	AFFF
Propelling Agent	N ₂	
Working Pressure	12-15 Bar	
Testing Pressure	30 Bar	
Coating	Electrostatic Polyester Powder	
Storage Temperature	5°C to 60°C	