

Portable Foam



Note:

Model SN.F6, SN.F9

Approved

AL-SANAD Portable Foam Fire Extinguishers are characterized for their quick fire suppression and extinguishing capabilities, especially oil, petrol and other liquid fire.

It works by covering a burning flammable liquid with a blanket of foam, cutting off the fire's air supply and preventing the release of flammable vapours.

Portable foam extinguishers are generally used as first attack fire fighting units which are suitable for class A and B fires.

Technical Specifications:

- ☞ Extinguishing Agent : AFFF
- ☞ Propelling Agent : N2/Air
- ☞ Working Pressure : 12 - 15 Bar
- ☞ Test Pressure : 30 Bar
- ☞ Coating : Electrostatic Polyester Powder
- ☞ Storage Temperature : 5°C to +60°C

Class of Fire:



A Solid matters forming glowing residues. e.g. wood, rubber (car tires), paper, textiles.



B Liquid combustible matter e.g. petrol, oils, grease, ether, alcohol.



CAUTION:
NOT FOR USE ON LIVE
ELECTRICAL EQUIPMENT

Model	SN.F6	SN.F9
Capacity	6 Ltr	9 Ltr
Total Weight (Kg)	9.71	14.4
Total Height with Base (mm)	605	645
Total Width (mm)	210	210
Cylinder Height (mm)	510	540
Cylinder Diameter (mm)	150	185
Hose Length (mm)	480	625
Maximum Effective Range (m)	5-6	5-6
Duration of Discharge (Sec)	25-30	30-40

Special Internal Coating:



The Internal part of the extinguisher has been coated with special plastic coat, integrated by Whirl Sintering process.